

Indala Mid-Range Card Readers

- ▶ **Indala FlexSecur® Technology for the Industry's Most Secure Proximity Readers** - Exclusive Indala FlexSecur Password-Protected Security between card and reader screens out unauthorized cards prior to sending access control data to the host system.
- ▶ **Superior Format Control for the Most Application Choices** - Indala products offer card formats of up to 172 bits, and readers configurable for Wiegand, Magstripe, and Serial output formats.
- ▶ **Indala Mid-Range Series Readers are Part of an Expansive Product Portfolio That Meets Every Proximity Reader Requirement** – The HID Indala Proximity portfolio includes classic, mullion/slim, wallswitch, mid-range, long-range, and heavy-duty keypad readers for every application.



ACCESS choice.

The Indala 125 kHz Mid-Range Reader product line is HID's latest offering of highly-secure proximity readers. The HID Indala Mid-Range reader, with FlexSecur® technology, is designed for applications requiring a longer read range of up to 12 inches. These high-quality Indala Proximity Readers deliver outstanding and consistent performance with intelligent programming technology, a uniform core module, and a range of stylish bezel designs including Arch and Wave in a variety of colors.

Exclusive FlexSecur® Security Technology

All HID Indala 125 kHz Proximity Readers feature FlexSecur technology, which provides an added level of access system security through a verification process at the reader. A unique HID Indala product feature, FlexSecur screens out unauthorized cards prior to sending access control data to the host system.

This additional verification step enhances the security of your access system in two ways:

1. The entire card data field is encrypted prior to programming the card. Therefore, the data on the card cannot be decoded to determine the actual information on the card. Only the reader is able to decrypt the data and transmit it to the access control system.
2. Cards and readers can be programmed uniquely for each site, protecting the end user against unauthorized entry attempts by using cards from another facility. Again, a feature unique to the HID Indala product line.

Key Features:

- ▶ The Mid-Range reader can be mounted on both U.S. style single and double gang back boxes.
- ▶ Suitable for indoor and outdoor use.
- ▶ The larger size reader gives a longer read range than the HID Indala Mullion or Wallswitch readers, while offering the same modern design in a variety of bezel choices.

Features

Many Reader Bezel Style Choices for Design Flexibility

Indoor / Outdoor Flexibility

Audio Tone Programming Flexibility

Compatible with Any Control Panel

Stylish readers are available in many attractive, "snap-on" bezel styles and colors.

All readers are fully potted and have weatherproof electronics assemblies, making them suitable for internal and external applications.

Standard, independently controllable audio tone is not tied to LED function.

Wiegand or Magnetic Stripe (Clock & Data) output easily interfaces with most existing access-control panels.

Unbeatable Warranty and Technical Support

Customers can select HID Indala 125 kHz Proximity Readers with confidence because HID offers a lifetime product warranty and global Technical Support.

Card Programming


The ProxSmith® Programmer System and Application Programming Interface puts flexibility and convenience in the hands of OEM and security professionals. With the ability to quickly program a card or reader on site, users no longer need to rely on the factory for custom formatted cards or readers. Plus, the ProxSmith Programmer System delivers the high level of security you expect from the HID Indala product line.

Mid-Range Readers

Mounting	Metal or plastic single or double gang outlet box	
Dimensions	Arch - 5.1"H x 6.1"W x 1.1"T (13.0 x 15.5 x 2.8 cm); Wave - 5.5"H x 6.4"W x 1.4"T (14.0 x 16.3 x 3.5 cm)	
Power Supply	4-14VDC	
Current Requirements	117 mA	
Operating Temperature	-31° F to 149° F (-35° C to 65° C)	
Operating Humidity	0-95% RH, non-condensing	
Transmit Frequency	125 kHz	
Certifications	UL294/cUL, FCC (US), Canada, CE Mark (Europe), Australia C-Tick, New Zealand EMC	
Base Part Number	Product Description	Package Part # *
610 Core Module: FP-0200A and FP-0200S (Serial)	Wave, Black	FP-1231A
	Wave, Blue	FP-1234A
	Wave, Black (Serial)	FP-1231S
	Wave, Blue (Serial)	FP-1234S
	Arch, Black	FP-3231A
	Arch, Grey	FP-3235A
	Arch, White	FP-3236A
	Arch, Beige	FP-3237A
	Arch, Black (Serial)	FP-3231S
	Arch, Grey (Serial)	FP-3235S
	Arch, White (Serial)	FP-3236S
	Arch, Beige (Serial)	FP-3237S
		Bezel Only Part #
	FPZ-1231A	
	FPZ-1234A	
	FPZ-1231A	
	FPZ-1234A	
	FPZ-3231A	
	FPZ-3235A	
	FPZ-3236A	
	FPZ-3237A	
	FPZ-3231A	
	FPZ-3235A	
	FPZ-3236A	
	FPZ-3237A	
Options	Color – Wave: Black, Blue, Arch: Black, Grey, White, Beige Selectable Output Type: Wiegand, ABA Track II, Serial TTL (requires use of BIL 232/422 Module) Standard Termination – wire pigtail Programmable: Yes	
Warranty	Lifetime	
Read Ranges**	FlexISO® Card	Up to 12" (30 cm)
	FlexISO XT Card	Up to 12" (30 cm)
	FlexCard®	Up to 12" (30 cm)
	FlexTag™	Up to 7" (17 cm)
	FlexKey®	Up to 7" (17 cm)
	FlexISO MIFARE®	Up to 12" (30 cm)
	FlexISO DESFire™	Up to 12" (30 cm)
	FlexISO iCLASS®	Up to 12" (30 cm)

* Includes bezel and core module
**Note: Dependent upon installation conditions.

Specifications are subject to change without notice.
© 2007 HID Global Corporation. All rights reserved. HID, the HID logo, Indala, ProxSmith, FlexSecur and iCLASS are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 4/2007



MKT-MIDRANGE-DS-EN



ACCESS experience.

hidcorp.com

HID Global Offices:

Corporate North America
9292 Jeronimo Road
Irvine, CA 92618-1905
U.S.A.
Phone: (800) 237-7769
Phone: (949) 598-1600
Fax: (949) 598-1690

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Phone: +852 3160-9800
Fax: +852 3160-4809

Latin America
Circunvalacion Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Phone: +52 477 779 1492
Fax: +52 477 779 1493

Europe, Middle East & Africa
Homefield Road
Haverhill, Suffolk
CB9 8QP
England
Phone: +44 (0) 1440 714 850
Fax: +44 (0) 1440 714 840